

Interactive Flat Panel (IFP) - Specifications

| | Model | INC55-C05E15 | INC65-C05E15 | INC75-C05E15 | INC85-C05E15 | INC98-C05E17 |
|--------------------------|---|--|---|--|--|---|
| Display | Resolution Viewable Size Viewing Angle Brightness Contrast Panel / Made Life Time Surface Protection Dimension | 4K - 3840 pixel x 2160 pixel (16:9) 1209.6mm(H) x 680.4mm(V), 55 Inch Horizontal Angle ≥ 178° Vertical Angle ≥ 178° Indoor usage, ≥ 350cd/m ² ≥ 3000:1 TFT-LCD, LED Backlight / LG or Samsung ≥ 50000 Hours 3mm Tempered Glass 1304mm x 800mm x 97mm | 4K - 3840 pixel x 2160 pixel (16:9) 1432.48mm(H) x 803.52mm(V), 65 Inch Horizontal Angle ≥ 178° Vertical Angle ≥ 178° Indoor usage, ≥ 350cd/m ² ≥ 4000:1 TFT-LCD, LED Backlight / LG ≥ 50000 Hours 3mm Tempered Glass 1523mm x 924mm x 98mm | 4K - 3840 pixel x 2160 pixel (16:9) 1650.24mm (H) x 928.26mm (V), 75 Inch Horizontal Angle ≥ 178° Vertical Angle ≥ 178° Indoor usage, ≥ 360cd/m ² ≥ 4000:1 TFT-LCD, LED Backlight / SHARP or LG ≥ 50000 Hours 3mm Tempered Glass 1764mm x 1043mm x 100mm | 4K - 3840 pixel x 2160 pixel (16:9) 1860.48mm(H) x 1046.52mm(V), 84 Inch Horizontal Angle ≥ 178° Vertical Angle ≥ 178° Indoor usage, ≥ 360cd/m ² ≥ 1800:1 TFT-LCD, LED Backlight / LG or SHARP ≥ 50000 Hours Toughened glass with level 7 of Mohs standard 1978mm x 1187mm x 100mm | 8K - 7680 x 4320 pixel (16:9) 2158.84mm(H) x 1214.35mm(V), 98 Inch Horizontal Angle ≥ 178° Vertical Angle ≥ 178° Indoor usage, ≥ 360cd/m ² ≥ 1800:1 TFT-LCD, LED Backlight / LG ≥ 50000 Hours Toughened glass with level 7 of Mohs standard 2257mm x 1335mm x 118mm |
| Built in computer | CPU Memory HDD External Memory Video Output Connect Video Output Connect Extended Connect Internet Wi-Fi Sound Output Language | Intel i5 4G DDRIII 120SSD / 500HDD USB Memory, SD Card or SATA Connect Memory HDMI, VGA 6 x USB (4 x USB 2.0 + 2 x USB 3.0) 1 x RJ45, 802.11b/g/n Audio-out English, & multi-language | Intel i5 4G DDRIII 120SSD / 500HDD USB Memory, SD Card or SATA Connect Memory HDMI, VGA 6 x USB (4 x USB 2.0 + 2 x USB 3.0) 1 x RJ45, 802.11b/g/n Audio-out English, & multi-language | Intel i5 4G DDRIII 120SSD / 500HDD USB Memory, SD Card or SATA Connect Memory HDMI, VGA 6 x USB (4 x USB 2.0 + 2 x USB 3.0) 1 x RJ45, 802.11b/g/n Audio-out English, & multi-language | Intel i5 4G DDRIII 120SSD / 500HDD USB Memory, SD Card or SATA Connect Memory HDMI, VGA 6 x USB (4 x USB 2.0 + 2 x USB 3.0) 1 x RJ45, 802.11b/g/n Audio-out English, & multi-language | Intel i7 8G DDRIII 120SSD / 500HDD USB Memory, SD Card or SATA Connect Memory HDMI, VGA 6 x USB (4 x USB 2.0 + 2 x USB 3.0) 1 x RJ45, 802.11b/g/n Audio-out English, & multi-language |
| Software | CPU system OS HD Video Support Video Format Image Format HTML IFP Built in OS Customise-able Remote Control | Windows 7/8 home – trial version installed Support up to 3840P MPEG1 / MPEG2 / MPEG4 / AVI / VOB / WMV / DIVX / MOV JPG / JPEG / GIF / PNG / BMP Support HTML / ASP / JSP / PHP Android Mobile Desktop system Yes with full menu Yes | Windows 7/8 home – trial version installed Support up to 3840P MPEG1 / MPEG2 / MPEG4 / AVI / VOB / WMV / DIVX / MOV JPG / JPEG / GIF / PNG / BMP Support HTML / ASP / JSP / PHP Android Mobile Desktop system Yes with full menu Yes | Windows 7/8 home – trial version installed Support up to 3840P MPEG1 / MPEG2 / MPEG4 / AVI / VOB / WMV / DIVX / MOV JPG / JPEG / GIF / PNG / BMP Support HTML / ASP / JSP / PHP Android Mobile Desktop system Yes with full menu Yes | Windows 7/8 home – trial version installed Support up to 3840P MPEG1 / MPEG2 / MPEG4 / AVI / VOB / WMV / DIVX / MOV JPG / JPEG / GIF / PNG / BMP Support HTML / ASP / JSP / PHP Android Mobile Desktop system Yes with full menu Yes | Windows 7/8 home – trial version installed Support up to 3840P MPEG1 / MPEG2 / MPEG4 / AVI / VOB / WMV / DIVX / MOV JPG / JPEG / GIF / PNG / BMP Support HTML / ASP / JSP / PHP Android Mobile Desktop system Yes with full menu Yes |
| Interactive Touch | IR touch | 6 points writing and 20 points touch | 6 points writing and 20 points touch | 6 points writing and 20 points touch | 6 points writing and 20 points touch | 6 points writing and 20 points touch |
| Power | Power Surge | Max 0.5A during start up. 0.1A normal operating | Max 0.5A during start up. 0.1A normal operating | Max 0.5A during start up. 0.1A normal operating | Max 0.7A during start up. 0.15A normal operating | Max 0.7A during start up. 0.15A normal operating |
| Warranty | 1 year full warranty* | Normal usage circumstances | Normal usage circumstances | Normal usage circumstances | Normal usage circumstances | Normal usage circumstances |

Product Images:

